Customer Release Notes WorkCentre® 7525/7530/7535/7545/7556 General Release 061.121.224.18803

Revision Date: November 3, 2014

dc14rn3329crn

Software Release Details

System Software	Version
System Software	061.121.224.18803
Network Controller	061.124.18820
User Interface	061.124.18820



Important

There is a software patch available within the .zip file to resolve an OMNIKEY® 3021 card reader issue. There are revisions of the card reader that will not respond when connected to the MFP. The patch file also addresses an issue with Common Access Card reader detection when coming out of Power Saver Mode. Installation instructions can be found in the release note within the patch file 616540v2.zip.

Purpose

This release provides the following enhancements:

- Support added for Rijkspas and PIV II smart cards
- HID 5427 programmable card reader support added
- Numerous card reader and card interaction improvements
- Xerox Device Management now able to set language of local user interface
- Xerox Device Management now able to setup device's Sleep Mode Timer
- When using the Print From feature a user is now able to select multiple finishing options at the same time (collate, staple, and hole punch) on a single print job.
- Cloning feature now includes local user interface language
- Low Toner Warning can now be suppressed on local user interface
- Enabled Reduce/Enlargement % adjustment for Booklet Mode
- Added ability to immediately release locally held jobs when user authenticates at device
- Added the ability to enabled or disable the Log Off Confirmation screen that is currently shown when a user attempts to Log Off of the MFD.
- When a print job is held for resources the user will now have the option to change the media for that held job at the LUI in order for the job to just print.
- Secure PDF scanning now allows the addition of a password with 128 bit encryption
- Added ability for system administrator to map different LDAP servers to each Smartcard Domain Controller.
- Status of Services (Displayed, Not Displayed, Enabled, Disabled) is now consistent between the printed configuration report, the device user interface, and the web user interface

- The 'Send Diagnostic Information to Xerox' button is now disabled when not enrolled in Xerox Remote Print Services
- The device's web user interface can now be configured to require password authentication
- Copier defaults can now be set from the device's web user interface and via the MIBs
- Added embedded support for USB connected Honeywell[®] 3800g Barcode Scanner
- Barcode printing improvements when using SAP
- Added ability to name Custom Paper Types
- Services such as Internet Fax, Server Fax, Scan to Email, and Workflow Scanning can now be disabled
- Remote Service Settings are now persistent across software upgrades/downgrades, and power off/on
- Failure report can now be suppressed when the a scan job fails for original size failures
- Numerous improvements to SMB scanning including network authentication, scanning to Windows Server 2012
- A number of improvements when printing from PCL6 including grey area printing
- Secure Access interaction improvements
- Scan template improvements
- Numerous EIP improvements
- Improvements when switching the default language of a device
- Number of Foreign Device Interface improvements
- Now able to scan into Microsoft[®] Windows[®] Server 2008 cluster share folder
- Scan to Home improvements
- Improved speed of Searchable Text/OCR scan
- Improved email function
- Fax number sent now clears once fax is transmitted
- Duplex printing reliability improvements
- Color rendition in "Standard" mode for Postscript was improved to provide more realistic color for some jobs. Color rendition in "High Quality" and "Enhanced" modes of Postscript were unchanged.
- Increased speed when submitting XPS jobs
- Improved print quality, speed, and reliability when printing PDF file
- Device will now scan to an IBM[®] AIX[®] mainframe using Samba version 3.0.30
- You may now Suppress All Blank pages when printing from IBM[®] AS/400[®]
- Now prints from Wyse[®] Thin OS
- Now able to Automatically Select when a tray call occurs after a specific tray call is made
- Improved paper tray email alerts
- Improved video when paper jam occurs
- Printing speed improvements when printing 8.5" x 14" short edge feed to Office Finisher LX
- Improved Xerox[®] Standard Accounting functionality
- Improved font management
- SMB scanning reliability issues resolved with Novel® open enterprise server
- The clone file process now capture the 'service Registration', 'Image Overwrite', and Copy Services settings
- z/OS[®] mainframe print jobs now print correctly when the printer is defaulted to duplex
- Custom paper size setting is always retained through a power saver cycle
- Printing improvements when using Network Accounting
- Certificate Signing Requests generated by device now works in the Cisco® environment

- Corrected orientation when printing Booklet, Fold & Staple with covers
- Improved speed with copying mixed sized originals
- Now able to use a comma in file name for a scanned document
- Default host name now accepts underscore character
- NTP host name information is retained during a printer reboot
- Now able to choose Trusted Certificate in LDAP setup when the CN field is blank
- The number, period, and comma character can now be used in custom email attachment names

Software Release Details

Software and installation instructions are available from http://www.xerox.com.

© 2014 Xerox Corporation. All Rights Reserved. Xerox®, Xerox and Design®, and WorkCentre®, are trademarks of Xerox Corporation in the United States and/or other countries.

Other company trademarks are also acknowledged.