Kit Installation Instructions

XOG SPAR Team

Product(s): EX 550/560	Date: 9/2012
Title: 1.1sp3 Installation Instructions	Page: 1 of 1

Purpose

This software kit provides an EX550/560 software update in response to an EX550/560 SPAR. Refer to the included customer letter for more information.

In the event of an EX550/560 system reinstall this software patch should be reapplied.

Kit Contents

Qty.	Description
1	Kit Installation Instructions
1	Customer Letter
1	SP3.exe

Prerequisites

- Previous working knowledge with the EX550/560
- 1.1sp1
- 1.1sp2

Installation Instructions

NOTE: This software may be installed by the customer.

Install the EX550/560 sp3**.exe patch:**

__ 1. Install the **sp3** patch

　__ a. Double click on sp3.exe file

　__ b. At the Fiery Patch Download window, click [Next]

　__ c. At the License Agreement window, click [Accept]

　__ d. At the Fiery Logon window, type the Fiery administrator login password in the Password field

　　NOTE: *Do NOT change the User field; that value must be admin.*

　__ e. In the Hostname field, type in the IP address or hostname of the EX550/560 and select [Connect]

　__ f. At the Server Information window, select [Download]. The patch will be downloaded and installed

　__ g. At the Processing window, select [Next], wait for approximately one (1) minute

　__ h. On the final window, select [Reboot], then select [Finish]

　　NOTE: *The patch will not be installed until the EX550-560 is rebooted.*

__ 2. Verify that the patch is installed and wrap-up

　__ a. Once the Fiery status says "Idle," select [Server: Print Pages] from the CWS menu and print a configuration page.

　__ b. On the "System Update Log" sheet of the configuration pages, ensure that the patch sp3 is listed

NOTE: When executing **sp3.exe**, *if you choose* **Restart later** *when prompted by the Fiery Patch Downloader, please make sure you manually reboot the server for changes to take effect.*

NOTE: There is a uninstaller for sp3. Just double click on the uninstall_sp.exe and follow the instruction to remove sp3.