Recommended Xerox Materials for DocuColor 2240 / 1632 (EUROPE)

Revision 0.0, Publish Date: June 10th, 2002

Preliminary

Important Notes:

All media is listed by product, machine run mode, weight (standard gsm), re-order number, size, and tray runability. The additional information column is for hints and tips on how to run certain media applications.

Media recommendations made in this publication are based on qualification tests* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

- * Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 20-40%.
- *Machine reliability specifications may be affected by increased usage of the Heavyweight 1 mode and Heavyweight 2 modes. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox service representative can advise you on using Heavyweight 1 mode, Heavyweight 2 mode or special application media types for long duration copy/print runs.

For specifications and a description of the various media types discussed in this publication, please refer to the Color Material Usage Guide that comes with your equipment.

© 2002 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

