Recommended Xerox Materials List of WorkCentre 7232 / 7242

For use in Europe

Revision 1.1 - Issued October 2007

Important Notes:

All media is listed by product, paper type, paper tray settings - image quality, weight (standard gsm), re-order number, size, tray runability, and integrated office finisher runability. The additional information column is for hints and tips on how to run certain media applications.

Machine reliability specifications may be affected by increased usage of Heavyweight 1, Heavyweight 2, Coated 1, and Coated 2 modes. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox service representative can advise you on using Heavyweight 1, Heavyweight 2, Coated 1, and Coated 2 modes or special application media types for long duration copy/print runs

Environmental Conditions may require that coated paper be fed one sheet at a time through Tray 5, (Bypass/SMH). Relative Humidity greater than 40% could cause multifeeds. Output may require removal at 25 sheets in the tray when not using a finisher

The Integrated Office Finisher is capable of stapling at maxium (maxium number may decrease if paper weight is greater than 90 gsm): 50 Sheets of in B5, A4, or 16k in Long Edge Feed (LEF); or of A4 in Short Edge Feed (SEF) 30 Sheets of B4, A3, or 8K

If only papers which require Paper Tray Settings - Image Quality other than the default setting (Plain D) will be used, the administrator can change the default setting to match the Image Quality setting of the paper being used.

© 2007 Xerox Corporation. All rights reserved.

Xerox® and all Xerox product names and product names, and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

For the latest line of Xerox supplies contact your local Xerox representative or a recommended distributor. For the most recent version of this list visit our website at www.xerox.com, select "Country", then "Supplies".

Trays 1,2,3, TTM, SMH & HCF RML 10/15/07 A = Auto Duplex Full Color Integrated Office Finisher * Coated 1 (106 - 169 gsm Heavyweight 1 (106 - 169 gsm) WorkCentre B = Auto Duplex Monochrome Capable of Stacking Paper Type Transparency Plain / Bond / Recycled (64 - 105 gsm) 7232 & 7242 Coated 2 (170 - 216 gms Heavyweight 2 (170 - 216 gsm) Labe S = Simplex Only Capable of Stapling Paper Type M = Manual Duplex Europe Paper Types are selected when Paper Tray is closed V 1.1 SMH Paper Tray Integrated Office **HCF** 2TM TTM Media Paper Type Settings - Image Weight Re-Order # Type Size Finisher Additional Information Quality Stack Staple 2 3 2 3 5 6 003R91821 А3 A A A Α • 003R91802 (2 hole) A4 A A A A Α ***** Α • Xerox Business Paper Plain* Plain F 80 gsm 003R91820 A4 A A A A A Α Α • • 003R91823 (4 hole) A4 AAAAA Α • 003R91721 A3 A A A Α • • 003R91720 A4 A A A A Α ***** Plain* Plain F 80 gsm 003R91741 US Lega A A A Α • ٠ 003R91723 (4 hole) A4 A A A A A Α ***** Α 003R91853 Xerox Premier A3 A A A Plain* Plain F 90 gsm 003R91850 (4 hole) A4 Α • A A A A A Α • 003R91854 A4 A A A A A Α • A3 A A A 003R93609 ***** Plain* Plain F 100 asm 003R93608 A4 A A A A A Α Α • + Heavyweight 1 Heavyweight 1A 120 gsm 003R93007 A4 B B B B В ***** 003R93009 A4 B B B B В • Heavyweight 1 Heavyweight 1A 160 gsm Xerox Premier TCF Environmental conditions may require that this product be fed one sheet at a S S ٠ Heavyweight 2 Heavyweight 2A 200 gsm 003R93011 A4 S S М S 003R90208 A4 AAAAA Α Α • • Bond Plain A 80 gsm 003R91712 (4 hole) A4 A A A A A Α • ***** 003R90209 A3 A A A ***** • 003R90618 A3 AAAA Xerox Exclusive Bond Plain A 90 gsm 003R91845 (4 hole) A4 A A A A A Α Α • • 003R90600 A4 AAAAA Α Α ***** • 003R94574 A4 A A A A A Α ***** Bond Plain A 100 gsm 003R94573 • A3 AAA Α • 003R94568 A3 A A A Α • • Plain* Plain F 80 gsm 003R94567(4 hole) A4 AAAAA Α Α • • 003R94565 A4 Α AAAAA Α • • Xerox Recycled Supreme Plain* Plain F 90 asm 003R95156 A4 AAAAA Α + Plain* Plain F 100 gsm 003R95161 A4 AAAAA Α Α • A4 A A A A A 003R97661 ***** Plain Plain A 80 gsm 003R97662 A3 • AAAA Α • 003R97663 A4 AAAAA Α • Α • Plain Plain A 90 gsm 003R97664 A3 A A A • • Xerox Colour Impressions 003R97666 A4 AAAAA • Α Α • Plain 100 gsm Plain A 003R97667 A3 • A A A Heavyweight 1 Heavyweight 1A 120 asm 003R97669 A3 B B B В ***** 003R97990 A3 A A A • Bond Plain A 90 asm 003R97988 A4 AAAAA Α • Α • 003R97989 (4 hole) A4 AAAAA Α Α • ***** 003R97955 A3 A A A • Bond Plain A 100 gsm 003R97993 A4 A A A A Α • • 003R97954 (4 hole) A4 AAAAA Α Α • • Xerox Colotech+ 003R97959 А3 В GOLD BBB • Heavyweight 1 Heavyweight 1A 120 asm 003R97958 A4 B B B B B ***** В 003R97964 В В В Environmental conditions may require that this product be fed one sheet at a Heavyweight 1 Heavyweight 1A 160 gsm • 003R97963 A4 B B B B B В В • time 003R97968 М A3 S S S ***** • Heavyweight 2A 200 gsm Heavyweight 2

SSSSS

S

A4

003R97967

Xerox Colotech+	Bond	Plain A	90 gsm	003R94642 003R94641 003R97673 (4 hole)		A3 A4 A4	A A A A A A A A A A A A A A A A A A A	A A A	•	* *	
	Bond	Plain A	100 gsm	003R94647 003R94646 003R97674 (4 hole)		A3 A4 A4	A A A A A A A A A A A A A A A A A A A	A A A	•	* *	
	Heavyweight 1	Heavyweight 1A	120 gsm	003R94652 003R94651		A3 A4	B B B B B B	B B	•	*	
	Heavyweight 1	Heavyweight 1A	160 gsm	003R94657 003R94656		A3 A4	B B B B B B	B B	•	*	Environmental conditions may require that this product be fed one sheet at a time
	Heavyweight 2	Heavyweight 2A	200 gsm	003R94662 003R94661		A3 A4	S S S S S S	M M S	•	+	
Xerox Colotech+ Gloss Coated Xerox Colotech+ Silk Coated	Coated 1	Coated 1A	120 gsm	003R97574 003R97575	Coated 2	A4 A3	B B B B B B	B B	•		Environmental conditions may require that this product be fed one sheet at a time
	Coated 1	Coated 1A	140 gsm	003R97577 003R98578	Sides	A4 A3	B B B B B B B B B B B B B B B B B B B	B B	•		Environmental conditions may require that this product be fed one sheet at a time
	Coated 1	Coated 1A	120 gsm	003R97593 003R97592		A3 A4	B B B B B	B B	•		Environmental conditions amy require that this product be fed one sheet at a
	Coated 1	Coated 1A	140 gsm	003R97596 003R97595		A3 A4	B B B B B	B B	•		time.
Xerox Colotech+ Natural White	Bond	Plain A	100 gsm	003R97103 003R97102		A3 A4	A A A A A A	A A	•	*	
	Heavyweight 1	Heavy 1A	160 gsm	003R95957 003R95956	Natural White	A3 A4	B B B B B	B B	•	*	Environmental conditions may require that this product be fed one sheet at a time
	Heavyweight 2	Heavy 2A	200 gsm	003R95959 003R95958		A3 A4	S S S S S S	M S	•	*	Environmental conditions may require that this product be fed one sheet at a time
Xerox Universal Transparencies Plain	Transparency	Transparency		003R98220		A4	S S S S S	s s	•		Paper Type Transparency should be displayed on the User Interface for trays/Bypass. It is not recommended to output more than 20 tranparencies at a time. If Jams occur from Bypass tray, main trays should be used.
Xerox Colotech+ Labels	Label	Label		003R93874 003R95815 003R95813 003R93873 003R93872	8 Up 21 UP 4 Up 6 Up 1 Up	A4 A4 A4 A4 A4	S S S S S S S S S S S S S S S S S S S	\$ \$ \$ \$ \$ \$ \$ \$ \$ \$	•		Lables are not intended as the sole application of the machine.
Xerox Mono High Speed Labels	Label	Label	90 gsm	003R96284 003R96177	10 Up	A4 A4	S S S S S S S	S S	•		
Xerox DuraPaper Labels	Label	Label	95 gsm	003R97344	1 Up	A4	S S S S S	S S	•		

"For usage of these papers, machine administrator may change the default setting of the "Plain" Paper Type in the Image Quality section of the Paper Tray Settings from the default to "Plain A"

^{**} Integrated Office Finisher will staple maximum of: 50 sheets of Letter, Executive, B5(LEF), A4(LEF/SEF) or 16K papers 30 sheets of Legder/Tabloid [17x11], Legal [8.5x14], B4, A3, or 8K papers Stapling capability will depend upon weight of paper