



XEROX 1010 Fiery Installation Instructions

Direct Queue

1. Unzip the file and copy the fix file (generally ends in '.ps') to a PC that has the Command Workstation running.
2. In the Command Workstation* pulldown menu:
 - select **Job ->Download**
3. In the Download Window:
 - select the **fix file** that was just copied to the PC
 - select **ADD**; the fix file will appear in the 'Files to be downloaded' window
 - select **Direct Connection** from the Connection Type pulldown menu
 - select **Download**
4. Wait at least 60 seconds and select "**Reboot System**" using the Fiery LCD located at the printer.
5. Let the Fiery come to 'Idle'.
6. Repeat steps 4 and 5.
7. Print out the configuration page.
8. The 'Update Information' section will contain the fix number just installed.

*NOTE: If you do not have Command Workstation loaded onto a PC or the FACI kit, use the Customer Software CD to load the Command Workstation onto a PC.

(For additional information, see page 48 of the *EFI-Getting_Started_Guide-EX1010.pdf* on the *EFI Fiery EX 1010 Documentation* CD.)

If you do not have the Customer Software CD, open your Web Browser and enter the IP address of the Fiery:

- Select 'Installer'
- Select (double click) 'Command Workstation' in the 'Windows' section.
- Select 'Save' in the File Download window.
- Select 'Desktop'; 'Save'.
- Locate the 'cstaton.exe' file and double click to open.

(For additional information, see page 71 of the *EFI-Getting_Started_Guide-EX1010.pdf* on the *EFI Fiery EX 1010 Documentation* CD.)

