Version 1.1
May 2012

Xerox® D95/D110/D125 Copier/Printer

PDL Reference Guide



©2012 Xerox Corporation. All rights reserved. XEROX® and XEROX and Design® are trademarks of the Xerox Corporation in the United States and/or other countries.

Adobe® and PostScript® are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

BR1460

Table of Contents

Table of Contents iii
Overview 1
Using this Guide 3
PostScript Fonts 5
PCL 7
PCL/PJL Implementation 9
PJL Template 13
Sample PJL Headers 15
PCL/PJL Feature Dependencies/ Caveats 17
PCL Fonts 19

Overview 1

This document enables you to access the extended features of the D95/D110/D125 and in environments that do not have a custom driver.

NOTE: Some of the commands and syntax used in this document requires some familiarity with either PostScript® (PS) or Printer Command Language (PCL).

This document provides the Printer Description Language (PDL) commands and syntax for each feature. The following items are also included:

- A PS table that describes the PS features the Copier/Printer supports and the syntax to use the feature.
- A PCL tables that describes the PCL features the Copier/Printer supports and the syntax to use the feature.

This document is not intended to be a complete PS or PCL reference manual. It is a guide for using the PS and PCL commands with Copier/Printer.

Refer to these additional reference materials PostScript Language Reference Manual, Third Edition, ISBN 0-201-38922-8, PCL5 Printer Language Technical Reference Manual, Hewlett-Packard Manual and Printer Job Language Technical Reference Manual, Hewlett-Packard Manual.

Using this Guide 2

1. Search the Feature Table to determine whether the feature you wish to use is supported.
2. Verify that the feature is supported by the platform. For example, the Copier/Printer must have the Finisher option installed to use stapling commands.
3. Following across the table to find the syntax listed for the PDL examples shown. Read the Dependencies/Caveats section.

PostScript Fonts 3

The following PS fonts are resident with Adobe® interpreter:

Albertus	Gill Sans Italic	New Century Schoolbook Italic
Albertus Italic	Gill Sans Bold	New Century Schoolbook Bold
Albertus Light	Gill Sans Bold Italic	New Century Schoolbook Bold Italic
Antique Olive Roman	Gill Sans Light	NewYork
Antique Olive Italic	Gill Sans Light Italic	OCR-B Letterpress M
Antique Olive Bold	Gill Sans Extra Bold	Optima Roman
Antique Olive Compact	Gill Sans Condensed	Optima Italic
Apple Chancery	Gill Sans Condensed Bold	Optima Bold
Arial	Goudy Oldstyle	Optima Bold Italic
Arial Italic	Goudy Oldstyle Italic	Oxford
Arial Bold	Goudy Bold	Palatino Roman
Arial Bold Italic	Goudy Bold Italic	Palatino Italic
ITC Avant Garde Gothic Book	Goudy Extra Bold	Palatino Bold
ITC Avant Garde Gothic Book Oblique	Helvetica	Palatino Bold Italic
ITC Avant Garde Gothic Demi	Helvetica Oblique	Stempel Garamond Roman
ITC Avant Garde Gothic Demi Oblique	Helvetica Bold	Stempel Garamond Italic
Bodoni Roman	Helvetica Bold Oblique	Stempel Garamond Bold
Bodoni Italic	Helvetica Narrow	Stempel Garamond Bold Italic
Bodoni Bold	Helvetica Narrow Oblique	Symbol
Bodoni Bold Italic	Helvetica Narrow Bold	Tekton Regular
Bodoni Poster	Helvetica Narrow Bold Oblique	Times Roman
Bodoni Poster Compressed	Helvetica Condensed	Times Italic
ITC Bookman Light	Helvetica Condensed Oblique	Times Bold
ITC Bookman Light Italic	Helvetica Condensed Bold	Times Bold Italic
ITC Bookman Demi	Helvetica Condensed Bold Oblique	Times New Roman
ITC Bookman Demi Italic	Hoefler Text	Times New Roman Italic
Carta	Hoefler Text Italic	Times New Roman Bold
Chicago	Hoefler Text Black	Times New Roman Bold Italic

Clarendon Roman	Hoefler Text Black Italic	Univers 45 Light
Clarendon Bold	Hoefler Ornaments	Univers 45 Light Oblique
Clarendon Light	Joanna	Univers 55
Cooper Black	Joanna Italic	Univers 55 Oblique
Cooper Black Italic	Joanna Bold	Univers 65 Bold
Copperplate Gothic 32BC	Joanna Bold Italic	Univers 65 Bold Oblique
Copperplate Gothic 33BC	Letter Gothic	Univers 57 Condensed
Coronet	Letter Gothic Slanted	Univers 57 Condensed Oblique
Courier	Letter Gothic Bold	Univers 67 Condensed Bold
Courier Oblique	Letter Gothic Bold Slanted	Univers 67 Condensed Bold Oblique
Courier Bold	ITC Lubalin Graph Book	Univers 53 Extended
Courier Bold Oblique	ITC Lubalin Graph Book Oblique	Univers 53 Extended Oblique
Eurostile Medium	ITC Lubalin Graph Demi	Univers 63 Extended Bold
Eurostile Bold	ITC Lubalin Graph Demi Oblique	Univers 63 Extended Bold Oblique
Eurostile Extended No. 2	Marigold	Wingdings
Eurostile Bold Extended No. 2	Monaco	ITC Zapf Chancery Medium Italic
Geneva	ITC Mona Lisa Recut	ITC Zapf Dingbat
Gill Sans	New Century Schoolbook Roman	

PCL 4

This Copier/Printer supports PCL5e and PCL XL Color emulations that enable the features listed in the following table:

Feature	Description
Job Name	Job Name
Custom Paper Size	This command specifies the customer designated media size.
Media Size	This command specifies the size of media on which to print the job.
Media Source	This command specifies the tray to supply the job's media.
Output Location	Indicates the output bin where the print job is sent.
Stapling	This command indicates use and location of staple(s).
Punch	This command indicates hole punches for a print job on a device with hole punch capability.
Folding	This command indicates to fold the print job.
Booklet	This command enables you to print documents as small booklets. The pages are reordered sequentially and are oriented so that when they are folded, the paging is correct.
Quantity	Use this command to specify the number of collated sets of a document.
Resolution	This command sets the resolution value.
Bits Per Pixel	This command sets the color depth value.
Copies	Use this command to specify the number of uncollated sets of a document in a print job.
Simplex	Deliver one-sided output
Duplex	Deliver two-sided output
Orientation	Landscape or Portrait
Force Short Edge Feeding	The values indicate the feed edge to use.
Job Mode	Specify Job Mode
Job Type (Secure Print / Proof Print / Box Print)	You can specify Confidential Print or Proof Print
Interleaving Paper (Transparency Separator)	Insert blank sheet between OHP sheets.
Job Based Accounting	
Auditron	
Delay Print	Delays printing a job until the time specified by the command.

PCL/PJL Implementation

5

This section describes the PCL commands for specific features. This table lists each feature and the PCL syntax that is required to use the feature. Following this table are examples of how to use these commands and what the PCL file looks like.

Refer to these reference materials: PCL5 Printer Language Technical Reference Manual and Printer Job Language Technical Reference Manual, Hewlett-Packard Manual.

Feature	Implementation	Values
Job Name	@PJL SET JOBNAME = "jobname-string"	Where jobname-string is a maximum of 32 characters Exclude ["](22H) character
Custom Paper Size	Not in PJL command. You have to specify by PCL : <ESC>&l101A	Width of Custom Paper is specified by <ESC>&f#Iwhere # = decipoints for (100 - 330)mm. Length of Custom Paper is specified by <ESC>&f#J where # = decipoints for (148 - 488)mm. For instance: 4.25-inch x 5.5-inch will give <ESC>&f3060I3960J by 4.25-inch x 720 decipoints/inch = 3060 and 5.5-inch x 720 decipoints/inch = 3960.
Media Size	@PJL SET PAPER = value	Where value is one of the following: A5 = A5 (148 x 210mm) † A4 = A4 (210 x 297mm) A3 = A3 (297 x 420mm) † JISB5 = B5 (182 x 257mm) JISB4 = B4 (257 x 364mm) STATEMENT = Statement (5.5 x 8.5") † EXECUTIVE = Executive (7.25 x 10.5") † LETTER = Letter (8.5 x 11") JISEXEC = 8.5 x 13" LEGAL = Legal (8.5 x 14") LEDGER = Tabloid (11 x 17") SPECIALA4 = Special A4(226x310mm) † DT_SPECIALA3 = DT Special A3(310 x 432mm) † 12X18 = Oversized Tabloid (12 x 18") † SA3 = SRA3 (320 x 450mm) † 126X192 = 12.6 x 19.2"(320x488mm) † 13X18 = 13 x 18"(330.2x457.2mm) † 13X19 = 13 x 19"(330.2x482.6mm) †ROC16K = 16K (194 x 267mm) † ROC8K = 8K (267 x 388mm) † 16KAIGCO = 16K (195 x 270mm) † 8KAIGCO = 8K (270 x 390mm) † †: Whether each paper is available depends on NV memory setting. The following paper sizes are only available with Bypass tray. A6 = A6 (105 x 148mm) JISB6 = B6 (128 x 182mm) 8X10 = 8 x 10" SPANISH = 215 x 315mm 11X15 = 11 x 15" A4COVER = A4 Cover (223 x 297mm)

Feature	Implementation	Values
		LETTERCOVER = 9 x 11" JPOST = Postcard (100 x 148mm) JPOSTD = Postcard (148 x 200mm) POSTCARD = Postcard (4 x 6") 50X70 = 5 x 7"
	<ESC>&l int A	Where value is one of the following: 25 = A5 (148 x 210mm) † 26 = A4 (210 x 297mm) 27 = A3 (297 x 420mm) 45 = B5 (182 x 257mm) 46 = B4 (257 x 364mm) 41 = Statement (5.5 x 8.5") † 1 = Executive (7.25 x 10.5") † 2 = Letter (8.5 x 11") 18 = 8.5 x 13" 3 = Legal (8.5 x 14") 6 = Tabloid (11 x 17") 224 = Special A4(226x310mm) † 213 = Oversized Tabloid (12 x 18") † 197 = SRA3 (320 x 450mm) † 219 = 16K (194 x 267mm) † 220 = 8K (267 x 388mm) † †: Whether each paper is available depends on NV memory setting. The following paper sizes are only available with Bypass tray. 24 = A6 (105 x 148mm) 44 = B6 (128 x 182mm) 208 = 8 x 10" 43 = 215 x 315mm 217 = 11 x 15" 200 = A4 Cover (223 x 297mm) 201 = 9 x 11" 71 = Postcard (100 x 148mm) 72 = Postcard (148 x 200mm) 216 = Postcard (4 x 6") 204 = 5 x 7"
Media Source	@PJL SET MEDIASOURCE = value	Where value is one of the following: TRAY1: Feed from paper tray1 TRAY2: Tray2 TRAY3: Tray3 TRAY4: Tray4 TRAY5: Tray5 (Bypass)TRAY6: Tray6 TRAY7: Tray7
	<ESC>&l int H	Where int is one of the following: 0: Feed paper from default tray 4: Tray1 1: Tray2 5: Tray3 8: Tray4 20: Auto 2 or 3: Tray5 (Bypass) 21: Tray6 22: Tray7 39: Tray8(Interposer)
Output Location	@PJL SET OUTBIN = value	Where value is one of the following: MAINTRAY3: finisher top trayOUTBIN101: Finisher tray BOOKLETTRAY: booklet tray FOLDERTRAY: folder tray
	<ESC>&l int G	Where int is one of the following: 0: Automatic Selection 1: Main tray 4: finisher top tray 6: Finisher tray
Stapling	@PJL SET STAPLE = value	Where value is one of the following: TOPDUAL

Feature	Implementation	Values
		TOPLEFT TOPRIGHT BOTTOMDUAL BOTTOMLEFT BOTTOMRIGHT LEFTDUAL RIGHTDUAL SADDLE TOPQUAD BOTTOMQUAD LEFTQUAD RIGHTQUAD NONE
Punch	@PJL SET PUNCH = value1 @PJL SET JOBATTR = "@PNHN = value2"	Where value1 is one of the following: TOP RIGHT LEFT BOTTOM NONE Where value2 is one of the following: TWO: 2 holes THREE: 3 holes FOUR: 4 holes
Folding	@PJL SET JOBATTR = "@FOLD = value1"	Where value1 is one of the following: BIFOLDINSIDE : Bi-Folding(single page) BIFOLDMULTIOUTSIDE : Bi-Folding(multi page) The "Collated" feature needs to enabled for the booklet functions to work.
Booklet	@PJL SET JOBATTR = "@BKLT = value1" @PJL SET JOBATTR = "@BKSG = value2" @PJL SET JOBATTR = "@BKDN = int1" @PJL SET JOBATTR = "@BKTP = int2"	Where value1 is one of the following: NONEDIVIDE : Compile a booklet as long as the number of sheet does not exceed the limit AUTODIVIDE : Divide sheets into sets automatically in case of exceeding the limit number of sheets. MANUALDIVIDE : Divide sheets based on the specified limit manually OFF : Do not compile a booklet Where value2 is one of the following: RIGHT : Right to left page order binding LEFT : Left to right page order binding Where int1 is: 1-9999 : Booklet dividing number for each set Where int2 is: 1-9999 : Booklet total pages of document
Quantity	@PJL SET QTY = int	Where int is: 1-999 (If you use this parameter, it also indicate use collate mode automatically.)
Resolution	@PJL SET RESOLUTION = value	Where value is one of the following: 600 1200
Bits Per Pixel	@PJL SET BITSPERPIXEL = value	Where value is one of the following: 1: 1 bit per pixel (per plane)
Copies	@PJL SET COPIES = int	Where int is: 1-999 (This parameter used for uncollated mode.)
	<ESC>&l int X	Where int is: 1-999
Simplex	@PJL SET DUPLEX = value1	Where value1 is one of the following: OFF: simplex
	<ESC>&l int S	Where int is one of the following: 0: simplex
Duplex	@PJL SET DUPLEX = value1 @PJL SET BINDING = value2	Where value1 is one of the following: ON: duplex Where value2 is one of the following: LONGEDGE SHORTEDGE (value2 is used combined with value1=ON)

Feature	Implementation	Values
	<ESC>&l int S	Where int is one of the following: 1: Duplex Long Edge Binding 2: Duplex Short Edge Binding
Orientation	@PJL SET ORIENTATION = value	Where value is one of the following: PORTRAIT LANDSCAPE
	<ESC>&l int O	Where int is one of the following: 0: Portrait 1: Landscape 2: Reverse Portrait 3: Reverse Landscape
Force short edge feeding	@PJL SET PAPERDIRECTION = value	Where value is one of the following: SEF: Short Edge Feed LEF: Long Edge Feed
Job Mode	@PJL JOB MODE = value	Where value is one of the following: PRINTER: for Printer
Job Type (Secure Print / Proof)	@PJL SET HOLD = value1 @PJL SET HOLDKEY = "string"	Where value1 is one of the following: PROOF: proof print STORE: confidential print (secure print) The HOLDKEY variable acts as a password without encryption to protect a held job. string is a maximum of 16 character (legal value 20H-FFH) as password without encryption. The default value is “”. When “”(empty string) is specified, no password is required.
Interleaving Paper (Transparency Separator)	@PJL SET SLIPSHEET = value	Where value is one of the following: OFF: no slipsheet BLANK: blank slipsheet COPY: imaged slipsheet
Job Based Accounting	@PJL SET JOBATTR = “@JOAU = string1” @PJL SET JOBATTR = “@JOAP = string2” @PJL SET JOBATTR = “@DAID = string3”	Where string1 is a maximum of 32 character (legal value: 20H-7EH) as job owner (Capital character & small character is distinguished) Where string2 is a maximum of 12 character (legal value: 20H-7EH) as password without encryption. It can be null (zero length string) Where string3 is a maximum of 32 character (legal value 20H-7EH) as account ID. It can be null (zero length string)
Auditron	ditto	ditto
Delay Print	@PJL SET JOBATTR = “@PRTM = YYYY:MM:DD:hh:mm”	YYYY:MM:DD:hh:mm YYYY: year(AD 2000～2099) MM: month (1～12) DD: day (1～31) hh: hour(0～23) mm: minute(0～59)
Banner Sheet	@PJL SET JOBATTR= “@BANR=value”	Where value is one of the following: START: start sheet DEVICE: depend on device setting OFF: no banner sheet

PJL Template

6

This section illustrates a standard PJL template that is used to access general print features as well as Copier/Printer Product specific features. This template lists each feature and the syntax, both PCL commands and PJL, required to use these features. The next section of this document contains other examples of how to use these commands.

Section 1 (Opening Command, Required for all files)

<ESC> %-12345X@PJL JOB MODE=PRINTER

Section 2 (PJL Set Commands)

@PJL SET RESOLUTION=600
@PJL SET COPIES=1

Section 3 (PCL Code used to invoke PCL Language)

@PJL ENTER LANGUAGE=PCL

Section 4 (PCL Data Stream or ASCII Document inserted here for Options such as selection Different Fonts, Simplex, Duplex, etc.)

,,,,,,,,,

Section 5 (Closing Command, Required at end of Document)

<ESC> %-12345X@PJL EOJ

Sample PJL Headers 7

Example 1 Simple Print

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL COMMENT Beginning PCL Job<CR><LF>
@PJL SET OUTBIN=MAINTRAY<CR><LF>
@PJL SET QTY=1<CR><LF>
@PJL SET RESOLUTION=600<CR><LF>
@PJL SET JOBATTR=”@JOAU=Nagaoka” <CR><LF>

Example 2 Finishing Options (Stapling)

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET OUTBIN=OUTBIN101<CR><LF>
@PJL SET FINISH=ON<CR><LF>
@PJL SET STAPLE=TOPLEFT<CR><LF>

Example 3 Finishing Options (Punch)

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET OUTBIN=OUTPIN101<CR><LF>
PJL SET FINISH=ON<CR><LF>
@PJL SET PUNCH=LEFT<CR><LF>
@PJL SET JOBATTR="@PNHN=TWO"<CR><LF>

Example 4 Finishing Options (Saddle stapling and folding)

It is an example of division in every 5 sheets.

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET OUTBIN=BOOKLETTRAY<CR><LF>
@PJL SET FINISH=ON<CR><LF>
@PJL SET STAPLE=SADDLE<CR><LF>
@PJL SET JOBATTR="@FOLD=BIFOLDMULTIOUTSIDE"<CR><LF>
@PJL SET JOBATTR="@BKLT=MANUALDIVIDE"<CR><LF>
@PJL SET JOBATTR="@BKSG=LEFT"<CR><LF>
@PJL SET JOBATTR="@BKDN=5"<CR><LF>

Example 5 Finishing Options (Bi-Folding(multi page))

It is an example of division in every 5 sheets.

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET OUTBIN=BOOKLETTRAY<CR><LF>
@PJL SET FINISH=NONE<CR><LF>
@PJL SET STAPLE=NONE <CR><LF>
@PJL SET JOBATTR="@FOLD=BIFOLDMULTIOUTSIDE"<CR><LF>
@PJL SET JOBATTR="@BKLT=MANUALDIVIDE"<CR><LF>
@PJL SET JOBATTR="@BKSG=LEFT"<CR><LF>
@PJL SET JOBATTR="@BKDN=5"<CR><LF>

@PJL SET QTY=1<CR><LF>

Example 6 Finishing Options (Bi-Folding(single page))

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET OUTBIN=BOOKLETTRAY<CR><LF>
@PJL SET FINISH=NONE<CR><LF>
@PJL SET STAPLE=NONE <CR><LF>
@PJL SET JOBATTR="@FOLD=BIFOLDINSIDE"<CR><LF>
@PJL SET JOBATTR="@BKSG=LEFT"<CR><LF>

Example 7 Proof Print

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET HOLD=PROOF <CR><LF>
@PJL SET USERNAME="John" <CR><LF>
@PJL SET JOBNAME="Job1" <CR><LF>

Example 8 Confidential (Secure) Print without encryption

Password: 1234

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET HOLD=STORE <CR><LF>
@PJL SET HOLDKEY="1234"<CR><LF>
@PJL SET USERNAME="John" <CR><LF>
@PJL SET JOBNAME="Job1" <CR><LF>

Example 9 Banner Sheet

banner : start sheet

@PJL SET JOBATTR=”@BANR=START”<CR><LF>
@PJL SET JOBATTR=”@BCMT=Banner Comment String”<CR><LF>

Example 10 Job Based Accounting & Auditron

userID:Patricia, Password: none, accountID: none

<ESC> %-12345X@PJL JOB MODE=PRINTER<CR><LF>
@PJL SET JOBATTR=”@JOAU=Patricia”<CR><LF>
@PJL SET JOBATTR=”@JOAP=”<CR><LF>
@PJL SET JOBATTR=”@DAID=”<CR><LF>

8 PCL/PJL Feature Dependencies/ Caveats

All PJL commands must be in the first 2,500 bytes of the job.

To combine printer escape commands (not including PJL commands):

The first two characters after the <esc> MUST be the same.

All alpha characters MUST be lowercase, except the final terminating character.

The commands are read left to right. Combine commands in the order you wish them to execute.

For example, combine print 5 copies (<ESC>&l5X) and use letter size (<ESC>&l2A) as <ESC>&l5x2A.

In case of duplicate commands, the last one requested takes precedence.

The @PJL SET COPIES takes precedence over the PCL Escape Command (<ESC>& l int X>) to set copies. In general, a PJL command takes precedence over a PCL command.

Valid media sizes for duplexing are between 139.7 x 182.0mm and 330.0 x 488.0mm.

Valid media sizes for stapling include A4 (210 x 297mm), A3 (297 x 420mm), B5 (182 x 257mm), B4 (257 x 364mm), Executive (7.25 x 10.5"), 8 x 10", Letter (8.5 x 11"), 215 x 315mm, 8.5 x 13", Legal (8.5 x 14"), 11 x 15", Tabloid (11 x 17"), A4 Cover, 9 x 11", Special A4(226x310mm), 16K (194 x 267mm), 8K (267 x 388mm), 16K (195 x 270mm), 8K (270 x 390mm) for Finisher D.

PCL Fonts

9

The following PCL fonts are resident.

Each of these commands references a 12-point font. If you wish to use any other point size, change the 12v to the desired size (.25 – 999.75).

The commands listed use the default symbol set, Roman-8. To change the symbol set, you include the alternate symbol set after the first <ESC> and before the second <ESC>. Use the line printer examples as a reference.

Font Name	PCL Escape Command
Albertus Medium	<esc>(<esc>(s1p12v0s1b4362T
Albertus Extra Bold	<esc>(<esc>(s1p12v0s4b4362T
Antique Olive	<esc>(<esc>(s1p12v0s0b4168T
Antique Olive Bold	<esc>(<esc>(s1p12v0s3b4168T
Antique Olive Italic	<esc>(<esc>(s1p12v1s0b4168T
Arial	<esc>(<esc>(s1p12v0s0b16602T
Arial Bold	<esc>(<esc>(s1p12v0s3b16602T
Arial Italic	<esc>(<esc>(s1p12v1s0b16602T
Arial Bold Italic	<esc>(<esc>(s1p12v1s3b16602T
CG Times	<esc>(<esc>(s1p12v0s0b4101T
CG Times Bold	<esc>(<esc>(s1p12v0s3b4101T
CG Times Italic	<esc>(<esc>(s1p12v1s0b4101T
CG Times Bold Italic	<esc>(<esc>(s1p12v1s3b4101T
CG Omega	<esc>(<esc>(s1p12v0s0b4113T
CG Omega Bold	<esc>(<esc>(s1p12v0s3b4113T
CG Omega Italic	<esc>(<esc>(s1p12v1s0b4113T
CG Omega Bold Italic	<esc>(<esc>(s1p12v1s3b4113T
Clarendon Condensed	<esc>(<esc>(s1p12v4s3b4140T
Coronet	<esc>(<esc>(s1p12v1s0b4116T
Courier	<esc>(<esc>(s1p12v0s0b4099T
Courier Bold	<esc>(<esc>(s1p12v0s3b4099T
Courier Italic	<esc>(<esc>(s1p12v1s0b4099T
Courier Bold Italic	<esc>(<esc>(s1p12v1s3b4099T
Garamond Antiqua	<esc>(<esc>(s1p12v0s0b4197T
Garamond Halbfett	<esc>(<esc>(s1p12v0s3b4197T
Garamond Kursiv	<esc>(<esc>(s1p12v1s0b4197T
Garamond Kursiv Halbfett	<esc>(<esc>(s1p12v1s1b4197T
Line Printer (Roman-8)	<esc>(8U<esc>(s0p16.67h8.5v0s0b0T
Line Printer (Latin-1)	<esc>(0U<esc>(s0p16.67h8.5v0s0b0T

Font Name	PCL Escape Command
Line Printer (PC-8)	<esc>(10U<esc>(s0p16.67h8.5v0s0b0T
Line Printer (PC-8 D/N)	<esc>(11U<esc>(s0p16.67h8.5v0s0b0T
Line Printer (PC-850)	<esc>(12U<esc>(s0p16.67h8.5v0s0b0T
Line Printer (Legal)	<esc>(1U<esc>(s0p16.67h8.5v0s0b0T
Marigold	<esc>(<esc>(s1p12v0s0b4297T
Times New	<esc>(<esc>(s1p12v0s0b16901T
Times New Bold	<esc>(<esc>(s1p12v0s3b16901T
Times New Italic	<esc>(<esc>(s1p12v1s0b16901T
Times New Bold Italic	<esc>(<esc>(s1p12v1s3b16901T
Symbol	<esc>(19M<esc>(s1p12v0s0b16686T
Wingdings	<esc>(579L<esc>(s1p12v0s1b31402T
Univers Bold	<esc>(<esc>(s1p12v0s3b4148T
Univers Bold Italic	<esc>(<esc>(s1p12v1s3b4148T
Univers Bold Condensed	<esc>(<esc>(s1p12v4s3b4148T
Univers Bold Condensed Italic	<esc>(<esc>(s1p12v5s3b4148T
Univers Medium	<esc>(<esc>(s1p12v0s0b4148T
Univers Medium Italic	<esc>(<esc>(s1p12v1s0b4148T
Univers Medium Condensed	<esc>(<esc>(s1p12v4s0b4148T
Univers Medium Condensed Italic	<esc>(<esc>(s1p12v5s0b4148T
Letter Gothic	<esc>(<esc>(s1p12h0s0b4102T
Letter Gothic Italic	<esc>(<esc>(s1p12h1s0b4102T
Letter Gothic Bold	<esc>(<esc>(s1p12h0s3b4102T
Times Roman	<esc>(<esc>(s1p12h0s3b4102T
Times Italic	<esc>(<esc>(s1p12h0s3b4102T
Times Bold	<esc>(<esc>(s1p12h0s3b4102T
Times Bold Italic	<esc>(<esc>(s1p12h0s3b4102T
Helvetica	<esc>(<esc>(s1p12v0s0b24580T
Helvetica Oblique	<esc>(<esc>(s1p12v1s0b24580T
Helvetica Bold	<esc>(<esc>(s1p12v0s3b24580T
Helvetica Bold Oblique	<esc>(<esc>(s1p12v1s3b24580T
CourierPS	<esc>(<esc>(s0p12h0s0b24579T
CourierPS Oblique	<esc>(<esc>(s0p12h1s0b24579T
CourierPS Bold	<esc>(<esc>(s0p12h0s3b24579T
CourierPS Bold Oblique	<esc>(<esc>(s0p12h1s3b24579T
SymbolPS	<esc>(19M<esc>(s1p12v0s0b45358T
Palatino Roman	<esc>(<esc>(s1p12v0s0b24591T
Palatino Italic	<esc>(<esc>(s1p12v0s0b24591T
Palatino Bold	<esc>(<esc>(s1p12v0s0b24591T
Palatino Bold Italic	<esc>(<esc>(s1p12v0s0b24591T

Font Name	PCL Escape Command
ITC Bookman Light	<esc>(<esc>(s1p12v0s-3b24623T
ITC Bookman Light Italic	<esc>(<esc>(s1p12v1s-3b24623T
ITC Bookman Demi	<esc>(<esc>(s1p12v0s2b24623T
ITC Bookman Demi Italic	<esc>(<esc>(s1p12v1s2b24623T
Helvetica Narrow	<esc>(<esc>(s1p12v4s0b24580T
Helvetica Narrow Oblique	<esc>(<esc>(s1p12v5s0b24580T
Helvetica Narrow Bold	<esc>(<esc>(s1p12v4s3b24580T
Helvetica Narrow Bold Oblique	<esc>(<esc>(s1p12v5s3b24580T
New Century Schoolbook Roman	<esc>(<esc>(s1p12v0s0b24703T
New Century Schoolbook Italic	<esc>(<esc>(s1p12v1s0b24703T
New Century Schoolbook Bold	<esc>(<esc>(s1p12v0s3b24703T
New Century Schoolbook Bold Italic	<esc>(<esc>(s1p12v1s3b24703T
ITC Avant Garde Book	<esc>(<esc>(s1p12v0s0b24607T
ITC Avant Garde Book Oblique	<esc>(<esc>(s1p12v1s0b24607T
ITC Avant Garde Demi	<esc>(<esc>(s1p12v0s2b24607T
ITC Avant Garde Demi Oblique	<esc>(<esc>(s1p12v1s2b24607T
ITC Zapf Chancery Medium Italic	<esc>(<esc>(s1p12v1s0b45099T
ITC Zapf Dingbats	<esc>(<esc>(s1p12v0s0b45101T